

## Certificate of Conformity

Certificate Number: CN-PVES-240471

On the basis of the tests undertaken, the sample<s> of the below product have been found to comply with the requirements of the referenced specification<s>/standard<s> at the time the tests were carried out. It does not imply that Intertek has performed any surveillance or control of the manufacture(s). The manufacturer(s) shall ensure that the manufacturing process assures compliance of the production units with the examined products mentioned in this certificate.

Applicant: Huawei Digital Power Technologies Co., Ltd.

Office 01, 39th Floor, Block A, Antuoshan Headquarters Towers, 33 Antuoshan 6th Road, Futian District, Shenzhen, 518043, P.R.China.

Product: Smart PCS

Ratings & Principle See appendix of Certificate of Conformity Characteristics:

Model: PCS2000-108K-MB1

Brand Name<s>:

**Product Complies with:** IEC61683:1999 Photovoltaic systems – Power conditioners – Procedure for

measuring efficiency

Certificate Issuing Office Intertek Testing Services Ltd. Shanghai

Name & Address: West Area, 2<sup>nd</sup> Floor, No. 707, Zhangyang Road

China (Shanghai) Pilot Free Trade Zone, Shanghai, P. R. China Accredited by ACCREDIA in accordance with ISO/IEC 17065:2012

**Test Report No.<s>:** 240718005GZU-001, 14 October 2024

Additional information in Appendix.

Signature

**Certification Manager: Grady Ye** 

(suste

Date: 18 Oct. 2024

ACCREDIA TALIANO DI ACCREDITAMENTO

PRD N° 306B



## **APPENDIX: Certificate of Conformity**

This is an Appendix to Certificate of Conformity Number: CN-PVES-240471

Model	PCS2000-108K-MB1
Max. Input voltage	1100Vdc
Max. Continuous current	187.1A
DC voltage operating range	550 – 950Vdc
Nominal voltage	380/400/415Vac, 3(N)~ 420/440/480Vac, 3(N)~
Nominal operating frequency	50/60Hz
Rated power	108kW
Rated apparent power	108kVA
Max. apparent power(5s)	140.4kVA
Rated current	164.1A/380Vac, 155.9A/400Vac 150.3A/415Vac,148.5A/420Vac 141.8A/440Vac, 130.0A/480Vac
Nominal output frequency	50/60 Hz
Power factor range	1Leading ~ 1Lagging
Safety level	Class I
Ingress protection	IP55
Operation ambient temperature	-25°C - +65°C
Software version	LUNA2000B V200R024C00

This Certificate is for the exclusive use of Intertek's client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this Certificate. Only the Client is authorized to permit copying or distribution of this Certificate. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek.